

# total control



## DMS-100

### Single Zone Amplifier

50 watts per channel amplifier for speakers ■ Preamp output for connection to local amp or receiver ■ One (1) audio input streams to other Total Control amplifiers ■ Scalable solution; install as additional zones with a DMS-1200 system, or install multiple DMS-100s to create customized multi-zone system ■ Can be programmed off premises via the internet and MRX-10 ■ Easy rack-mounting via optional RMK-1 rack mounting kit



# DMS-100 Multi-zone Amplifier



## specifications

* Network	One 10/100 Ethernet port (Indicator 2LED)
* IR One Way & IP Two Way Control	YES
* Indicators	1 Power BLUE LED - Blink when resetting / 1 Network BLUE LED Indicates
* Zones of Stereo Audio	One (preamp and speaker output are linked)
* Rated Wattage per Channel	50 watts per channel 2 8 ohms, stable to 4 ohms
* Automatic Low Volume Loudness Compensation	Installer Configured for Type and Size of Audio Zone
* Installer Configured EQ	Bass Boost, Treble Boost, 5-Band parametric EQ,
* Input sensitivity	600~2200mVp-p / 10Kohm
* User Adjustable Audio Controls	Bass, Treble and Balance
* Receives All SNP and DMS Generated Streams	Yes
* Inputs	1 Stereo Line INPUT streams to all other DMS Amplifiers
* Preamp Output	Yes, configurable to Fixed Line Level Output
* Power Supply	AC 100~245V, 50/60Hz
* Power consumption	1~2A
* Maximum external Dimensions	1.7" x 17" x 8.7"(H X W x D)
* Weight	7 lbs. (3.2Kg)